

US009636629B2

(12) United States Patent

Lake et al.

(54) REAL-TIME ONLINE DETERMINATION OF CAUSTIC IN PROCESS SCRUBBERS USING NEAR INFRARED SPECTROSCOPY AND CHEMOMETRICS

(71) Applicant: SABIC Global Technologies B.V.,

Bergen op Zoom (NL)

(72) Inventors: Derek Lake, Evansville, IN (US);

Yusuf Sulub, Newburg, IN (US);
Zhensheng Ding Mt Vernon IN (

Zhensheng Ding, Mt. Vernon, IN (US)

(73) Assignee: SABIC GLOBAL TECHNOLOGIES

B.V., Bergen op Zoom (NL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/722,429

(22) Filed: May 27, 2015

(65) Prior Publication Data

US 2015/0251131 A1 Sep. 10, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/971,748, filed on Aug. 20, 2013, now Pat. No. 9,084,975. (Continued)

(51) Int. Cl. *G01J 5/02* (2006.01) *B01D 53/14* (2006.01)

(Continued)

(52) **U.S. CI.**CPC **B01D 53/1493** (2013.01); **B01D 53/1412**(2013.01); **B01D 53/1456** (2013.01);
(Continued)

(10) Patent No.: US 9,636,629 B2

(45) **Date of Patent:** May 2, 2017

(58) Field of Classification Search

CPC B01D 2251/304; B01D 53/1412; B01D 53/1456; B01D 53/1493; B01D 53/346;

(Continued)

(56) References Cited

U.S. PATENT DOCUMENTS

4,121,103 A * 10/1978 Calhoun G01F 23/2921

250/339.05

4,563,427 A 1/1986 Weiss et al. (Continued)

OTHER PUBLICATIONS

ABB Analytical—PIR3502 Multiwave process photometer: Caustic monitoring in acid gas scrubbers, ABB Inc., 2011, 2 pp., http://www05.abb.com/global/scot/scot205.nsf/veritydisplay/d94b6c8560672d5c852578fe004a7855/\$file/a_n%20pir3502%20caustic%20monitoring%20in%20acid%20gas%20scrubbers

%2081620!!.pdf (last visited Nov. 22, 2013).

(Continued)

Primary Examiner — David J Makiya Assistant Examiner — Taeho Jo

(74) Attorney, Agent, or Firm — Baker & Hostetler LLP

(57) ABSTRACT

The present invention is to provide processes, apparatuses, and systems for monitoring and/or controlling caustic concentrations in caustic scrubbers. In various aspects, the processes, apparatuses, and systems comprise a real-time online method for measuring the concentration of caustic in process scrubbers wherein a probe is coupled to a spectrometer; collecting absorption data with wavelength range from about 1000 to about 2000 nm. In a further aspect, this technique tracks the use and recharge of caustic in process scrubbers.

18 Claims, 7 Drawing Sheets

